



## Technical data: SR 21 AJ

### Specifications:

|                           |                   |
|---------------------------|-------------------|
| Platform height max.      | 21,00 m           |
| Horizontal reach max .    | 17,80 m           |
| Rotation                  | 360° continu      |
| Load capacity max.        | 227 kg            |
| Platform rotation         | 180° (90° + 90°)  |
| Jib range of articulation | 130° (+70°, -60°) |

### Dimensions:

|                             |                      |
|-----------------------------|----------------------|
| A. Platform size (standard) | 1,80 x 0,75 x 1,10 m |
| Platform size (optional)    | 2,40 x 0,75 x 1,10 m |

|                      |           |
|----------------------|-----------|
| B. Width             | 2,46 m    |
| C. Tailswing         | 1.13 m    |
| D. Height            | 2.35 m    |
| E. Length            | 11,57 m   |
| F. Wheelbase         | n.a.      |
| G. Ground clearance  | 0,425 m   |
| Gross vehicle weight | 15.200 kg |

**Driving:**

|                    |           |
|--------------------|-----------|
| Drive speed        | 2,0 km/u  |
| Gradeability max.  | 48% (26°) |
| Tires (foamfilled) | n.a.      |
| Oscillating axle   | n.a.      |

**Power source:**

|                    |                     |
|--------------------|---------------------|
| Name/type          | Isuzu A 4JB1, PA-22 |
| Output max.        | 44.3 kW/2.400 rpm   |
| Fuel tank capacity | 150 ltr             |

**Standard options:**

Track drive  
Drive speed control  
Rotation speed control  
Lift speed control  
Motion alarm  
Control panel protection