

MODELS	GS™-2668 DC		GS™-3268 DC	
DIMENSIONS	Metric	US	Metric	US
Working height maximum*	9,92 m	32 ft	11,75 m	38 ft
Platform height	7,92 m	26 ft	9,75 m	32 ft
Platform length - outside	2,51 m	8 ft 3 in	2,51 m	8 ft 3 in
extended	3,61 m	11 ft 8 in	3,61 m	11 ft 8 in
Slide-out platform extension	1,10 m	3 ft 6 in	1,10 m	3 ft 6 in
Platform width - outside	1,55 m	5 ft 1 in	1,55 m	5 ft 1 in
Footprint length	10 cm	4 in	10 cm	4 in
Platform height - stowed	1,13 m	3 ft 10,75 in	1,31 m	4 ft 3,75 in
Height - stowed	2,32 m	7 ft 6,5 in	2,57 m	8 ft 4 in
rails lowered	1,79 m	5 ft 7 in	1,65 m	5 ft
Length - stowed	2,67 m	8 ft 9 in	3,42 m	11 ft 2 in
platform extended	4,19 m	13 ft 9 in	4,19 m	13 ft 9 in
Width	1,73 m	5 ft 8 in	1,73 m	5 ft 8 in
Wheelbase	1,85 m	6 ft 1 in	1,85 m	6 ft 1 in
Ground clearance - centre	39 cm	15 in	39 cm	15 in
CAPACITIES				
Maximum platform occupancy (indoor/outdoor)	4/4	4/4	4/2	4/2
Lift capacity	567 kg	1,250 lbs	454 kg	1,000 lbs
Drive speed - stowed	4,8 km/h	3,0 mph	4,8 km/h	3,0 mph
Drive speed - raised**	0,4 km/h	0,3 mph	0,4 km/h	0,3 mph
Turning radius - inside	0 cm	0 in	0 cm	0 in
Turning radius - inside	1,52 m	5 ft	1,52 m	5 ft
Turning radius - outside	3,68 m	12 ft 1 in	3,68 m	12 ft 1 in
Raise/lower speed	30/30 sec	30/30 sec	40/37 sec	40/37 sec
Controls	proportional		proportional	
Tires	dual foam filled		dual foam filled	
Multiple drive motors	dual rear wheel		dual rear wheel	
Tyres - low profile foam filled tire†	32 x 9N cm	12,6 x 3,5 in	32 x 9N cm	12,6 x 3,5 in
Tyres - non-marking	23 x 12,5 cm	9 x 5 in	23 x 12,5 cm	9 x 5 in
POWER				
Power source	48 V DC (eight 225-Ah batteries)		48 V DC (eight 225-Ah batteries)	
Hydraulic system capacity	38 L	9,5 gal	38 L	9,5 gal
WEIGHT**				
	3,135 kg	6,909 lbs	3,790 kg	8,356 lbs
CE max	3,153 kg	6,951 lbs	3,721 kg	8,203 lbs
STANDARDS COMPLIANCE	CE EN280; PR-10-011-03			

Merkmale

Hersteller: Typbezeichnung:	
Bauart:	Scheren-Arbeitsbühne
Arbeitshöhe:	9,92 m
Plattformhöhe:	7,92 m
Max. seitl. Reichweite:	
Tragfähigkeit max.:	567,00 kg
Korb / Plattform drehbar?:	
Korblänge / Plattformlänge:	2,51 m
Plattformausschub:	1,10 m
Korbbreite / Plattformbreite:	1,55 m

Transportlänge:	2,67 m
Transportbreite:	1,73 m
Transporthöhe:	2,32 m
Eigengewicht / Gesamtgewicht:	3200,00 kg
Antrieb:	Elektro
Eignung für Außeneinsatz / Inneneinsatz:	Innen
Geländegängig:	nein
Steigfähigkeit:	30,00 %
Schwenkbereich der Arbeitsbühne:	
Raupen- oder Radmobil:	Rad